Ordering number:EN3570

N-Channel Silicon MOSFET

2SK1432

Ultrahigh-Speed Switching Applications

DISCONTINUED PRODUCT


Features

- Low ON-state resistance.
- Ultrahigh-speed switching.
- Converters.
- Micaless package facilitating easy mounting.

Package Dimensions

unit:mm

2063A



Specifications

Absolute Maximum Ratings at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		100	V
Gate-to-Source Voltage	V_{GSS}		±20	V
Drain Current (DC)	I_D		25	A
Drain Current (Pulse)	I_{DP}	PW≤10μs, duty cycle≤1%	100	A
Allowable Power Dissipation	P_D	Tc=25˚C	40	W
			2.0	W
Channel Temperature	Tch		150	˚C
Storage Temperature	Tstg		–55 to +150	˚C

Electrical Characteristics at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=1mA, V_{GS}=0	100			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=100V, V_{GS}=0			100	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±20V, V_{DS}=0			±100	nA
Cutoff Voltage	$V_{GS(off)}$	V_{DS}=10V, I_D=1mA	1.5		2.5	V
Forward Transfer Admittance	|yfs|	V_{DS}=10V, I_D=20A	13	22		S
Static Drain-to-Source ON-State Resistance	$R_{DS(on)}$	I_D=20A, V_{GS}=10V		0.040	0.055	Ω

(Note) Be careful in handling the 2SK1432 because it has no protection diode between gate and source.

Continued on next page.

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.


■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges,or other parameters) listed in products specifications of any and all SANYO products described or contained herein.


SANYO Electric Co.,Ltd. Semiconductor Company
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN


Continued from preceding page.


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Input Capacitance	Ciss	V_{DS}=20V, f=1MHz		2400		pF
Output Capacitance	Coss	V_{DS}=20V, f=1MHz		700		pF
Reverse Transfer Capacitance	Crss	V_{DS}=20V, f=1MHz		200		pF
Turn-ON Delay Time	$t_{d(on)}$	I_D=20A, V_{GS}=10V, V_{DD}=50V, R_{GS}=50Ω		30		ns
Rise Time	t_r	I_D=20A, V_{GS}=10V, V_{DD}=50V, R_{GS}=50Ω		90		ns
Turn-OFF Delay Time	$t_{d(off)}$	I_D=20A, V_{GS}=10V, V_{DD}=50V, R_{GS}=50Ω		320		ns
Fall Time	t_f	I_D=20A, V_{GS}=10V, V_{DD}=50V, R_{GS}=50Ω		130		ns
Diode Forward Voltage	V_{SD}	I_S=25A, V_{GS}=0			1.8	V


Switching Time Test Circuit
















DISCONTINUED PRODUCT

















DISCONTINUED

DISCONTINUED PRODUCT

- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data,services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of May, 1999. Specifications and information herein are subject to change without notice.